



GJL 3P
Circuit Breaker

Table 7.46: PowerPact G-frame 3P 100 A Thermal-magnetic Circuit Breaker (600Y/347 Vac)

Ampere Rating	Adjustable AC Magnetic Trip		J Interrupting		Terminal Wire Range
	Low	High	Cat. No.	\$ Price	
15 A	600 A	1200 A	GJL36015	1327.00	14-1/0 AWG Cu or 8-1/0 AWG Al
20 A	600 A	1200 A	GJL36020	1327.00	
30 A	600 A	1200 A	GJL36030	1327.00	
40 A	600 A	1200 A	GJL36040	1327.00	
50 A	800 A	1400 A	GJL36050	1327.00	
60 A	800 A	1400 A	GJL36060	1327.00	
70 A	800 A	1400 A	GJL36070	1632.00	
80 A	800 A	1400 A	GJL36080	1632.00	
90 A	800 A	1400 A	GJL36090	1632.00	
100 A	800 A	1400 A	GJL36100	1632.00	

Table 7.47: G-frame Interrupting Ratings

Voltage	J interrupting
240 Vac	100 kA
480 Vac	65 kA
600Y/347 Vac	18 kA

Table 7.48: PowerPact Q-frame 250 A Thermal-magnetic Circuit Breaker (240 Vac)

Ampere Rating	Fixed AC Magnetic Trip		B Interrupting		D Interrupting		G Interrupting		J Interrupting		Terminal Wire Range	
	Hold	Trip	Cat. No. ♦	\$ Price	Cat. No. ♦	\$ Price	Cat. No. ♦	\$ Price	Cat. No. ♦	\$ Price		
2P, 240 Vac												
70 A	1000 A	1800 A	QBL22070	316.00	QDL22070	762.00	QGL22070	1014.00	QJL22070	1260.00	#4 AWG - 300 kcmil Al/Cu	
80 A	1000 A	1800 A	QBL22080	316.00	QDL22080	762.00	QGL22080	1014.00	QJL22080	1260.00		
90 A	1000 A	1800 A	QBL22090	316.00	QDL22090	762.00	QGL22090	1014.00	QJL22090	1260.00		
100 A	1200 A	2400 A	QBL22100	316.00	QDL22100	762.00	QGL22100	1014.00	QJL22100	1260.00		
110 A	1200 A	2400 A	QBL22110	316.00	QDL22110	762.00	QGL22110	1014.00	QJL22110	1260.00		
125 A	1200 A	2400 A	QBL22125	316.00	QDL22125	762.00	QGL22125	1014.00	QJL22125	1260.00		
150 A	1200 A	2400 A	QBL22150	316.00	QDL22150	762.00	QGL22150	1014.00	QJL22150	1260.00		
175 A	1200 A	2400 A	QBL22175	316.00	QDL22175	762.00	QGL22175	1014.00	QJL22175	1260.00		
200 A	1200 A	2400 A	QBL22200	316.00	QDL22200	762.00	QGL22200	1014.00	QJL22200	1260.00		
225 A	1200 A	2400 A	QBL22225	316.00	QDL22225	762.00	QGL22225	1014.00	QJL22225	1260.00		
250 A	1200 A	2400 A	QBL22250 ■	462.00	QDL22250 ■	1029.00	QGL22250 ■	1313.00	QJL22250 ■	1565.00		
3P, 240 Vac												
70 A	1000 A	1800 A	QBL32070	832.00	QDL32070	1189.00	QGL32070	1628.00	QJL32070	1864.00		#4 AWG - 300 kcmil Al/Cu
80 A	1000 A	1800 A	QBL32080	832.00	QDL32080	1189.00	QGL32080	1628.00	QJL32080	1864.00		
90 A	1000 A	1800 A	QBL32090	832.00	QDL32090	1189.00	QGL32090	1628.00	QJL32090	1864.00		
100 A	1200 A	2400 A	QBL32100	832.00	QDL32100	1189.00	QGL32100	1628.00	QJL32100	1864.00		
110 A	1200 A	2400 A	QBL32110	832.00	QDL32110	1189.00	QGL32110	1628.00	QJL32110	1864.00		
125 A	1200 A	2400 A	QBL32125	832.00	QDL32125	1189.00	QGL32125	1628.00	QJL32125	1864.00		
150 A	1200 A	2400 A	QBL32150	832.00	QDL32150	1189.00	QGL32150	1628.00	QJL32150	1864.00		
175 A	1200 A	2400 A	QBL32175	832.00	QDL32175	1189.00	QGL32175	1628.00	QJL32175	1864.00		
200 A	1200 A	2400 A	QBL32200	832.00	QDL32200	1189.00	QGL32200	1628.00	QJL32200	1864.00		
225 A	1200 A	2400 A	QBL32225	832.00	QDL32225	1189.00	QGL32225	1628.00	QJL32225	1864.00		
250 A	1200 A	2400 A	QBL32250 ■	1208.00	QDL32250 ■	1628.00	QGL32250 ■	2100.00	QJL32250 ■	2310.00		

- ▲ Replacement lugs are not available for PowerPact Q-frame circuit breakers.
- 250 A lugs are suitable for copper conductors only
- ♦ DE2A Discount Schedule

Table 7.49: Q-frame Termination Options

Termination Letter
A = I-Line (See Section 9)
E = Bolt-on I-Line (See Section 9)
F = No Lugs (includes terminal nut kit on both ends)★
L = Lugs both ends
M = Lugs ON end, Terminal Nut Kit OFF end
P = Lugs OFF end, Terminal Nut Kit ON end

★ Add TS suffix for circuit breakers without terminal nut kit. See catalog 0734CT0204 for additional information.

For factory-installed termination, place termination letter in the third block of the circuit breaker catalog number.

QGL32200
L Termination Letter

Table 7.50: Q-frame Interrupting Ratings

Voltage	Interrupting Rating			
	B	D	G	J
240 Vac▼	10 kA	25 kA	65 kA	100 kA△

- ▼ Q-frame circuit breakers are 240 Vac only.
- △ 3P QJ circuit breakers are rated at 208Y/120 Vac only.

Accessories Page 7-35
 Optional Lugs Page 7-38
 Dimensions Page 7-54
 Enclosures Page 7-55



QBL 2P
70-250 A



QBL 3P
70-250 A

MINIATURE AND MOLDED CASE
CIRCUIT BREAKERS